

Material Safety Data Sheet

1. Identification of the material and supplier:

Product name COOLANT ANTIFREEZE 50%

SDS no. 00150

Product use For specific application advice see appropriate Technical Data Sheet or

consult our company representative.

Supplier DAMAM General Trading FZCO

P.O BOX 452939

LB181402, JAFZA VIEW 18, Jebel Ali Free Zone, Dubai, United Arab

Emirates

Tel: +971 4 321 9009 Fax: +971 4 343 0776 Email: info@damam.ae

EMERGENCY TELEPHONE +971 4 321 9009 **Product code** PAT00150

2. Hazards identification:

Statement of NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

hazardous/dangerous nature

3. Composition/information on ingredients:

Ethylene glycol Corrosion inhibitor.

Chemical nameCAS no.% (V/V)ClassificationEthylene glycol; ethanediol107-21-150 %Xn; R22

This product does not contain any hazardous ingredients at or above regulated thresholds.

MSDS: COOLANT ANTIFREEZE 50% Page 1 of 8



4. First-aid measures:

Eye contact In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Eyelids should be held away from the eyeball to ensure

thorough rinsing. Check for and remove any contact lenses.

Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognized skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse.

Clean shoes thoroughly before reuse. Get medical

attention if irritation develops.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms appear.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get

medical attention if symptoms occur.

Advice to doctor Treatment should in general be symptomatic and directed to relieving any

effects.

5. Fire-fighting measures:

Extinguishing media In case of fire, use foam, dry chemical or carbon dioxide extinguisher or

Suitable spray.

Not suitable Do not use water jet.

Hazardous decomposition Decomposition products may include the following materials:

products carbon dioxide

carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides.

Unusual fire/explosion In a fire or if heated, a pressure increase will occur and the container may

hazards bur

Special fire-fighting No action shall be taken involving any personal risk or without suitable

procedures training. Promptly isolate the scene by removing all persons from the

vicinity of the incident if there is a fire.

Protection of fire-fighters Fire-fighters should wear appropriate protective equipment and self-

contained breathing apparatus (SCBA) with a full face-piece operated in

positive pressure mode.



6. Accidental release measures:

Personal precautions No action shall be taken involving any personal risk or without suitable

training. Evacuate surrounding areas.

Keep unnecessary and unprotected personnel from entering.

Do not touch or walk through spilt material. Put on appropriate personal

protective equipment (see Section 8).

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Large spill Stop leak if without risk. Move containers from spill area. Prevent entry

into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth,

vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal

contractor.

Small spill Stop leak if without risk. Move containers from spill area. Dilute with water

and mop up if water-soluble.

Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed

waste disposal contractor.

7. Handling and storage:

Handling Put on appropriate personal protective equipment.

Storage Store and use only in equipment/containers designed for use with this

product. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible

materials (see Section 10).

Combustibility Classification Combustible liquid Class C2 (AS 1940).

MSDS: COOLANT ANTIFREEZE 50% Page **3** of **8**



8. Exposure controls/personal protection:

Ingredient name

Ethylene glycol; ethanediol

Occupational exposure limits

EH40-WEL (United Kingdom (UK), 1/2005). Skin

STEL: 104 mg/m3 15 minute(s). Form: Vapor TWA: 10 mg/m3 8 hour(s). Form: Particulate TWA: 52 mg/m3 8 hour(s). Form: Vapor

Whilst specific OELs for certain components are included in this SDS, it should be noted that other components of the preparation will be present in any mist, vapor or dust produced. For this reason, the specific OELs may not be applicable to the product and are provided for guidance purposes.

Biological Limit Values

Exposure controls

Occupational exposure controls

No biological limit allocated.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organization for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are

compatible.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products,

before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation

location.

Personal protective equipment

Respiratory protection

Skin and body

_

Hand protection

Avoid breathing of vapors, mists or spray. Select and use respirators in accordance with AS/NZS 1715/1716. When mists or vapors exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapors and dust/mist (Type P1) filters. Filter capacity and respirator type depends on exposure level.

Avoid prolonged or repeated contact with skin. Wear protective clothing if

prolonged or repeated contact is likely.

Wear protective gloves if prolonged or repeated contact is likely. Chemical-

resistant gloves. Recommended: nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore, be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

Eye protection Safety glasses with side shields.



9. Physical and chemical properties:

Physical state Liquid. Color Green. Odour Alcohol-like. >100 °C. Flash point рΗ 8.10. >100 °C. **Boiling point / range** Freezing point / range -37. Concentration 50 %.

Relative density/Specific gravity Not available.

Density 1060 kg/m3 (1.06 g/cm3) at 15°C.

Solubility Miscible in water.

10. Stability and reactivity:

Stability The product is stable.

Conditions to avoid Avoid extreme temperatures, strong oxidizers, fire.

Incompatibility with various substances/Hazardous Reactions

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides.



11. Toxicological information:

Effects and symptoms

Eyes No significant health hazards identified.

Skin Prolonged or repeated contact can defeat the skin and lead to irritation

and/or dermatitis.

InhalationNo significant health hazards identified.IngestionNo significant health hazards identified.

Chronic toxicity

Other chronic toxicity data USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene

maintained.

Carcinogenic effects No component of this product at levels greater than or equal to 0.1% is

identified as a carcinogen by ACGIH, the International Agency for Research

on Cancer (IARC), the European Commission (EC).

Mutagenic effects No known significant effects or critical hazards.

Incompatibility with various substances/Hazardous Reactions

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides phosphorus oxides

metal oxide/oxides.

12. Ecological information:

Ecotoxicity Not classified as environmentally hazardous in accordance with the

'Approved Criteria for Classifying Hazardous Substances' [NOHSC

(1008)/2004 as amended and adapted].

Biodegradability

Persistence/degradability

The biodegradability of this material has not been determined.

MSDS: COOLANT ANTIFREEZE 50% Page 6 of 8



13. Disposal considerations:

Disposal considerations / Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration No additional special precautions identified.

14. Transport information:

International transport regulations

Special precautions for user

Not classified as dangerous for transport (ADG, IMDG, ICAO/IATA).

No known special precautions required. See Section: "Handling and storage" for additional information.

15. Regulatory information:

Standard for the Uniform

Scheduling of Medicines and

Poisons
Substances of very high concern

Annex XVII - Restrictions on the manufacturer, placing on the market and use of certain

dangerous substances, mixtures

and articles

Other regulations REACH Status

For the REACH status of this product please consult your company contact,

Consumer products - This product is exempt per Appendix A of the SUSMP.

as identified in Section 1.

Not scheduled.

Not applicable

United States inventory

(TSCA 8b)

All components are listed or exempted.

Australia inventory (AICS)
Canada inventory

China inventory (IECSC)
Japan inventory (ENCS)

At least one component is not listed. At least one component is not listed.

MSDS: COOLANT ANTIFREEZE 50%



16. Other information:

Key to abbreviations

AMP = Acceptable Maximum Peak.

ACGIH = American Conference of Governmental Industrial Hygienists, an agency that promulgates exposure standards.

ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail. ADG Code = Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number = Chemical Abstracts Service Registry Number.

HAZCHEM Code = Emergency action code of numbers and letters which gives information to emergency services. Its use is required by the ADG Code for Dangerous Goods in bulk.

ICAO = International Civil Aviation Organization.

IATA = International Air Transport Association, the organization promulgating rules governing shipment of goods by air.

IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.

IP 346 = A chemical screening assay for dermal toxicity. The European Commission has recommended that Method IP 346 be used as the basis for labelling certain lubricant oil base stocks for carcinogenicity. The EU Commission has stipulated that classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. (See Note L, European Commission Directive 67/548/EEC as amended and adapted.) DMSO is a solvent. NOHSC = National Occupational Health & Safety Commission, Australia.

TWA = Time weighted average. STEL = Short term exposure limit.

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

History

Date of Issue 01-Jun-2023.
Date of Revision 01-Sep-2023.

Prepared by Product Stewardship.

Notice to reader:

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from PATRON. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. PATRON shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact PATRON to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

MSDS: COOLANT ANTIFREEZE 50% Page 8 of 8