

PATRON TRANSTRON DEXRON III

(FULLY SYNTHETIC)

PRODUCT DESCRIPTION :

PATRON TRANSTRON DEXRON III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability .

APPLICATION :

PATRON TRANSTRON DEXRON III is Suitable for automatic gearboxes of passenger cars, heavy-duty automatic transmissions, power steering units and hydraulic systems requiring DEXRON III G and Allison C-4 fluids .

FEATURES & BENEFITS:

- It provides protection against the formation of lacquers, sludge or other harmful deposits.
- Exceptional stability provided by excellent base oil and extra oxidation inhibitors.
- Especially effective in minimizing transmission "chatter." It helps ensure smooth, and quiet action at all speeds.
- It ensures fast circulation during cold weather and excellent lubrication when hot.

OEM Approvals:

- ZF TE-ML 04D, 14A.
- VOITH H55.6335.xx.

PERFORMANCE LEVELS / MEETS AND EXCEEDS :

- GM DEXRON III G, III H
- ZF TE-ML 14A, 03D, 04D, 17C, 09C
- VOITH H55.6335.xx
- VOITH 55.6336.3x
- MAN 339 TYPE V1/Z1/V2/Z2
- MB 236.9/236.1/236.5/236.6/236.10
- ALLISON TES-389
- VOLVO 97340, 97341
- FORD M, FORD TASA
- ALLISON C4

TYPICAL PERFORMANCE :

PARAMETERS	TEST METHOD	UNIT	PATRON TRANSTRON DEXRON III
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	34.50
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7.25
Viscosity Index	ASTM D-2270	-	180
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.850
Flash Point (min)	ASTM D-92	°C	200
Pour Point (max)	ASTM D-97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.