



PATRONTM

POWER TO ACHIEVE

www.patronlubricants.ae

Product Catalog

GASOLINE ENGINE OILS | DIESEL ENGINE OILS | INDUSTRIAL OILS
GEAR & TRANSMISSION | MARINE OILS | GREASES | SPECIALTIES PRODUCTS



GASOLINE ENGINE OILS ————— **04**



DIESEL ENGINE OILS ————— **05**



INDUSTRIAL OILS ————— **06**



GEAR & TRANSMISSION ————— **07**



MARINE OILS ————— **11**



GREASES ————— **12**



SPECIALTIES PRODUCTS ————— **13**

PATRONTM

POWER TO ACHIEVE



About Us

PATRON Lubricants is in business to lead a prosperous partner network driven by innovative lubricant technology and a deep understanding of our industry's needs. PATRON Lubricants develops high-performance lubricants, fluids, greases and coolants.

With a state-of-the-art automated blending system with latest machineries to keep products precisely blended avoiding any human errors, ensuring consistency in the delivery of products in scheduled time without compromising in quality.

The advanced technology and logistics system allow unlimited opportunities for growth and guarantee of high-quality products coupled with greater ability to make faster deliveries across the world.

Our Engineers Have realized that a critical factor of success to specific industry knowledge, the company is founded and articulated by a team of leading industry professionals, strategic partners, and business associates, which in turn have encouraged and emboldened the company to participate in one of the most challenging markets in the world.

With a primary focus on the GCC, Middle East, Far East and Africa, PATRON Lubricants is uniquely positioned to lead in manufacturing, development and marketing in the regional and international markets, providing unmatched level of support and services for its customers.





PATRON
POWER TO ACHIEVE

- 12 x 1 Litre
- 24 x 1 Litre
- 6 x 4 Litre
- 4 x 5 Litre
- 6 x 5 Litre
- 20 Litre
- 208 Litre

PERFORMA HP PLUS

- 12
- 24
- 64
- 45
- 65
- 20
- 27

Classification: API: SN, SP

PATRON PERFORMA HP PLUS is an advanced fully synthetic engine oil designed to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high-performance gasoline engine cars equipped with direct-injection, multi valve and turbo-charger technologies.



FULLY SYNTHETIC

SAE Grade
0W-20
0W-30
5W-30
5W-40

Performance Levels (Meets & Exceeds) / OEMs:

- API Service Category SN, SP
- BMW LL-04
- MB 229.31, 229.52, 226.5
- PORSCHE C40
- VW 511 00
- GM DEXOS 2

PERFORMA HP

- 12
- 24
- 64
- 45
- 65
- 20
- 27

Classification: API: CH-4 / SL

PATRON PERFORMA HP engine oil is formulated from premium quality semi-synthetic base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. These premium engine oils contain ultra-pure base oils and a technologically advanced additive system which provides improved oxidation resistance, improved deposit protection, better wear protection, excellent low temperature performance and enhanced fuel economy.



SEMI SYNTHETIC

SAE Grade
10W-30
10W-40
15W-40
20W-50

Performance Levels (Meets & Exceeds) / OEMs:

- API Service Category CH-4 / SL
- GM DEXOS1
- FORD 947-B1
- ILSAC GF-6B



PATRON

POWER TO ACHIEVE



- 12 x 1 Litre
- 24 x 1 Litre
- 6 x 4 Litre
- 4 x 5 Litre
- 6 x 5 Litre
- 20 Litre
- 208 Litre

TURBOTRON HD

Classification: API: CI-4

PATRON TURBOTRON HD is a fully synthetic high-performance diesel engine oil developed to provide outstanding lubrication to modern, high performance diesel engines operating in severe on and off-highway applications. This product has been blended with highest performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control, and fuel economy improvement.



FULLY SYNTHETIC

SAE Grade
10W-40
15W-40

- 12
- 24
- 64
- 45
- 65
- 20
- 27

Performance Levels (Meets & Exceeds) / OEMs:

- ACEA E7, E4
- MACK E0-M Plus
- MB 228.5
- Cummins CES 20077/78
- MAN M3277
- Renault RXD/RLD-2
- Volvo VDS-3
- MTU Type 3
- Scania LDF-2

TURBOTRON RLX

Classification: API: CH-4

PATRON TURBOTRON RLX is a high-performance engine oil that provides proven protection to diesel engines operating in severe conditions for both on and Off-highway applications. This product has been blended with highest performance mineral base oils and fortified with an advanced additive system which assures superior control of oil thickening caused by soot buildup and high temperature oxidation.



MINERAL

SAE Grade
15W-40
15W-50
20W-50
20W-60
SAE 30
SAE 40
SAE 50


- 12
- 24
- 64
- 45
- 65
- 20
- 27

Performance Levels (Meets & Exceeds) / OEMs:

- API CH-4
- Renault RLD-2
- VOLVO VDS-2
- MB 228.3
- MTU Type 2
- Cummins CES 20076
- MAN 3275
- JASO DH1
- DFS 93K215
- ACEA E7, A3/B3/B4
- Mack E0-M/E0-L



PATRON
POWER TO ACHIEVE



INDUSTRIAL OILS

12 x 1 Litre

24 x 1 Litre

6 x 4 Litre

4 x 5 Litre

6 x 5 Litre

20 Litre

208 Litre

Hydraulic Oils

HYDRON HLP

Classification: HLP DIN 51524-2

PATRON HYDRON HLP hydraulic oil is a high viscosity index anti-wear hydraulic oil. It has been specially formulated to provide good anti-wear and thermal stability performance using the very latest additive technology. It provides excellent wear protection for hydraulic pumps and motors, has excellent oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life, and protects hydraulic system components against rust and corrosion.



12 24 64 45 65 20 27

MINERAL

ISO VG Grade

VG 22

VG 32

VG 46

VG 68

VG 100

Performance Levels (Meets & Exceeds) / OEMs:

- DIN 51524-2 HLP
- ASTM D6158-05 HM
- Eaton (Vickers) M-2950 S, I-286 S
- ISO 11158 HM

Turbine Oils

OPTIMA T

Classification: DIN 51524-1-2 / DIN 51515

PATRON OPTIMA T Turbine Oils are used in stationary gas turbines, steam turbines and also in electrical or in driven by steam machines such as generators, compressors, pumps and gearboxes. They can also be used for lubrication of hydraulic systems, compressors, gear transmissions, bearings and other industrial applications.



12 24 64 45 65 20 27

MINERAL

ISO VG Grade

VG 32

VG 46

VG 68

VG 100

Performance Levels (Meets & Exceeds) / OEMs:

- DIN 51515 TEIL 1 (L-TD), TEIL 2 (L-TG)
- TLV 901304
- MIL-L-17672 D
- BRITISH STANDARD BS 489
- GENERAL ELECTRIC GEK 32568 A
- GENERAL ELECTRIC GEK 32568 C
- CEGB STANDARD 207001
- BROWN BOVERI HTGD 90117
- U.S. STEEL 120
- WESTINGHOUSE ELECTRIC CORP. TURBINE OIL SPEC
- ALSTOM HTGD 90117 V0001 S
- DIN 51524-1 / 2



PATRON
POWER TO ACHIEVE

GEAR & TRANSMISSION

12 x 1 Litre

24 x 1 Litre

6 x 4 Litre

4 x 5 Litre

6 x 5 Litre

20 Litre

208 Litre

Industrial Gear Oil

ALPHATRON EP

Classification: Extreme Pressure / DIN 51517-3
PATRON ALPHATRON EP range have been formulated for use in all types of enclosed gears including heavy and shock-loaded gears and bearings where EP properties are required. They are suitable for use in industrial gear boxes including gear boxes where micro-pitting resistance is required and for a wide range of applications in extreme environments, for example mining and quarrying, marine, crushers, hoists, conveyors, winches applications.



12 24 64 45 65 20 27

MINERAL

ISO VG Grade

VG 68
VG 100
VG 150
VG 220
VG 320
VG 460
VG 680
VG 1000

Performance Levels (Meets & Exceeds) / OEMs:

- AGMA EP 9005-E02
- DIN 51517-3 (CLP)
- U.S. Steel 224 Specification (ISO 220, 320, 460, 680)
- FLENDER

Industrial Transmission Oil

TRANSTRON TO-4 HD

Classification: TO-4 HD

PATRON TRANSTRON TO-4 HD is specially designed for power shift transmissions, final drives and wet brakes on heavy duty off-highway equipment in earthmoving, mining, logging, road transport and agricultural applications. It is blended from premium quality base oils and proven performance additives.



12 24 64 45 65 20 27

FULLY SYNTHETIC

Grade


10W
30
50
60

Performance Levels (Meets & Exceeds) / OEMs:

- Caterpillar TO-4.
- Allison TES 439
- Komatsu KES 07.868.1
- Allison C-4
- ZF TE-ML-03C
- API GL-4



PATRON
POWER TO ACHIEVE



GEAR & TRANSMISSION

- 12 x 1 Litre
- 24 x 1 Litre
- 6 x 4 Litre
- 4 x 5 Litre
- 6 x 5 Litre
- 20 Litre
- 208 Litre

Automotive Gear Oil

ALPHATRON – GL4

Classification: API: GL-4

PATRON ALPHATRON provides an inherently high Viscosity Index (VI) and low pour points making these products suitable for use over a wide temperature range for the type of service characteristics of gears, particularly hypoid, in passenger cars and other Automotive type equipment, operated under high speed, low torque and low-speed/high torque conditions.



- 12
- 24
- 64
- 45
- 65
- 20
- 27

SEMI SYNTHETIC

SAE Grade

- 90
- 140
- 80W-90
- 85W-90
- 80W-140
- 85W-140
- 75W-90

Performance Levels (Meets & Exceeds) / OEMs:

- API: GL-4
- ZF TE-ML 08
- MAN 341 (TYPE MB)
- MB 235.11

ALPHATRON HD – GL5

Classification: API: GL-5

PATRON ALPHATRON HD is extra high-performance commercial gear lubricants which contain select base oils and a balanced additive system. ALPHATRON HD provide excellent chemical and thermal stability and good performance at low temperatures.



- 12
- 24
- 64
- 45
- 65
- 20
- 27

FULLY SYNTHETIC

SAE Grade

- 80W-90
- 85W-140
- 75W-90

Performance Levels (Meets & Exceeds) / OEMs:

- API: GL-5
- API MT-1
- MIL-PRF-2105E
- SAE J2360
- MAN 342 M2
- SCANIA STO 1:0
- ZF TE-ML 05A, 7A, 12E, 16B, C & D, 17B, 19B, 21A
- MB 235.8
- VOLVO 97312



PATRON
POWER TO ACHIEVE

GEAR & TRANSMISSION

12 x 1 Litre

24 x 1 Litre

6 x 4 Litre

4 x 5 Litre

6 x 5 Litre

20 Litre

208 Litre

Brake Fluid

FORCE DOT 4

Classification: DOT 4

PATRON FORCE DOT 4 is made from high molecular weight polyalkylene glycol ethers and borate esters, to give a high boiling point fluid of DOT 4 quality. The formulation has been developed in a way that the vapor lock point can be sustained at a higher level than conventional Glycol ether-based fluids during the service life of the product. It contains inhibitors to prevent the corrosion of metallic brake components and to reduce oxidation at increased temperatures.

12 24 64 45 65 20 27



FULLY SYNTHETIC

Grade
DOT 4

Performance Levels (Meets & Exceeds) / OEMs:

- FMVSS 116 DOT 3 and DOT 4
- ISO 4925 (Classes 3 & 4)
- SAE J 1703 and J 1704
- JIS K 2233

FORCE DOT 3

Classification: DOT 3

PATRON FORCE DOT 3 is high quality synthetic brake and clutch fluids conforming to the DOT3 specifications and are based on polyglycol type fluids that is a general standard used in worldwide automotive brake equipment. The product is blended with special additives that prevent fluid oxidation, rust and the swelling of the piston seals used in conventional brake systems.

12 24 64 45 65 20 27



FULLY SYNTHETIC


Grade
DOT 3

Performance Levels (Meets & Exceeds) / OEMs:

- FMVSS 116 DOT 3
- ISO 4925
- SAE J 1703



PATRON
POWER TO ACHIEVE



GEAR & TRANSMISSION

12 x 1 Litre

24 x 1 Litre

6 x 4 Litre

4 x 5 Litre

6 x 5 Litre

20 Litre

208 Litre

Transmission Fluid

TRANSTRON A

Classification: Type A

PATRON TRANSTRON A is a multi-purpose transmission fluid, designed for use in automatic gearboxes, where GM Type A Suffix A is quoted. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.



12 24 64 45 65 20 27

MINERAL

Specifications
Type A

Performance Levels (Meets & Exceeds) / OEMs:

- GM Type A Suffix A

TRANSTRON DEXRON III

Classification: DEXRON III

PATRON TRANSTRON DEXRON III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability.



12 24 64 45 65 20 27

FULLY SYNTHETIC

Specifications
DEXRON III

Performance Levels (Meets & Exceeds) / OEMs:

- GM DEXRON III, IIIH
- FORD MERCON V
- FORD ESP-M2C-138-CJ/166-H
- CHRYSLER ATF +3, ATF +4
- HONDA ATF Z-1
- PSA AL-4
- MB 236.12 / 14 / 15 / 41
- RENAULT DP-0

TRANSTRON DEXRON VI

Classification: DEXRON VI

PATRON TRANSTRON DEXRON VI is a fully synthetic transmission fluid recommended for use in passenger car and light truck automatic transmissions that require a GM DEXRON VI or earlier generation fluid. Transmissions include the following Aisin Warner models: AW TF-80SC / SD, AWF21, AF40-6, AM6, AW6A-EI, TF81SC, AF21, GA6F21WA (Mini).



12 24 64 45 65 20 27

FULLY SYNTHETIC

Specifications
DEXRON VI

Performance Levels (Meets & Exceeds) / OEMs:

- JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638
- AS 68RC (T IV)
- AUDI/VW
- G-052-162-A1/A2
- BMW ETL-7045, 7045E, LA2634, ETL-8072B, 81 22 9 400 275
- CHRYSLER M1375.4
- PEUGEOT ZF 4 HP20
- GENERAL MOTORS DEXRON II/III/IIIH/VI
- MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41
- PORSCHE ATF 3403-M115



PATRON
POWER TO ACHIEVE

- 12 x 1 Litre
- 24 x 1 Litre
- 6 x 4 Litre
- 4 x 5 Litre
- 6 x 5 Litre
- 20 Litre
- 208 Litre

COOLANT ANTIFREEZE

COOLANT ANTIFREEZE

Classification: Coolant

PATRON COOLANT ANTIFREEZE is a ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. PATRON COOLANT ANTIFREEZE is formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off road use.



Concentration

- 33%
- 50%
- 60%
- 100%

- 12
- 24
- 64
- 45
- 65
- 20
- 27

Performance Levels (Meets & Exceeds) / OEMs:

- BS 6580
- ASTM D3306
- SAE J1034, J1038
- Cummins 90T8-4
- CAT ELC (EC-1)
- Detroit Diesel 7SE298
- TMC RP329
- Freightliner 48-22880
- GM 1825, 1899M, 6277M



PATRON
POWER TO ACHIEVE



MARINE OILS

- 12 x 1 Litre
- 24 x 1 Litre
- 6 x 4 Litre
- 4 x 5 Litre
- 6 x 5 Litre
- 20 Litre
- 208 Litre

MARINE

Classification: API: CF

PATRON MARINE is formulated with high-quality bases oils and most advanced additive package to meet the latest design of Medium speed diesel engines burning residuals fuels in marine and stationary engines.



MINERAL

- ISO VG Grade
- MARINE 3030
- MARINE 3040
- MARINE 4030
- MARINE 4040
- MARINE 4055
- MARINE 4050
- MARINE 4055

- 12
- 24
- 64
- 45
- 65
- 20
- 27

Performance Levels (Meets & Exceeds) / OEMs:

- WÄRTSILÄ
- Caterpillar
- Yanmar
- Daihatsu
- MAN Diesel



PATRON

POWER TO ACHIEVE



GREASE

24 x 250 Gms

12 x 500 Gms

1 x 5 Kg

1 x 15 Kg

180 Kg

SEALATRON LITHIUM GREASE MP

Classification: LITHIUM MP GREASE

PATRON SEALATRON LITHIUM MP is a multi-purpose lithium-based grease containing friction reducing molybdenum disulphide. It is excellent for swivel and shackle lubrication. It also shows excellent performance in the lubrication of heavily loaded slow/medium speed bearings of all types and is particularly useful in preventing bearing damage caused by excessive vibration or shock loading.



71 72 73 74 98

MINERAL

NLGI Grade

- NLGI 00
- NLGI 0
- NLGI 2
- NLGI 3

Performance Levels (Meets & Exceeds) / OEMs:

- ISO 6743-9: L-XBCEA 2
- DIN 51 502: K2K -25

SEALATRON LITHIUM GREASE EP

Classification: LITHIUM EP GREASE

PATRON SEALATRON LITHIUM EP is a Lithium thickened lubricating grease formulated with mineral base oil and improved with extreme pressure (EP) additives to lubricate and protect even in heavy loaded circumstances. Mechanically very stable and easily pumpable due to its smooth consistency.



71 72 73 74 98

MINERAL

NLGI Grade

- NLGI 000
- NLGI 00
- NLGI 0
- NLGI 1
- NLGI 2
- NLGI 3

Performance Levels (Meets & Exceeds) / OEMs:

- ISO 6743-9: L-XBCEA 2
- DIN 51 502: K2K -25
- DIN 51825
- DIN 51826



PATRON
POWER TO ACHIEVE

SPECIALTIES PRODUCTS



- 12 x 1 Litre
- 24 x 1 Litre
- 6 x 4 Litre
- 4 x 5 Litre
- 6 x 5 Litre
- 20 Litre
- 208 Litre

OPTIMA NEAT CUTTING

Classification: Cutting Oil

PATRON OPTIMA NEAT CUTTING is a non-corrosive type all-purpose oil suitable for ferrous and non-ferrous applications and acts as an excellent metal working oil particularly for machining operations on automatics, where intense heat is generated at work, piece/tool interface, due to high spindle speeds and short cycle time. It contains active and non-active Sulphur, fatty oil and chlorinated additives to give better surface finish and longer life of cutting tools over a wide range of operating temperatures by providing an excellent lubricating film which resists cutting stresses.



- 12
- 24
- 64
- 45
- 65
- 20
- 27

MINERAL

ISO VG Grade
VG 22
VG 32

OPTIMA SOLUBLE CUTTING

Classification: Cutting Oil

OPTIMA SOLUBLE CUTTING is designed to help offer long service life, has low maintenance requirements and is suitable for a wide range of materials and operations. Offering the right balance between cooling and lubrication, OPTIMA Soluble Cutting Oils aims to deliver excellent tool life and surface finish, which can help reduce tool regrinding and component rejects.



- 12
- 24
- 64
- 45
- 65
- 20
- 27

MINERAL

ISO VG Grade
VG 46

OPTIMA QUENCHING

Classification: Quenching Oil

OPTIMA QUENCHING is a highly refined paraffin based quenching oil for the uniform hardening of carbon and alloy steels. The low viscosity of OPTIMA QUENCHING Oil enables fast oil circulation during heat transfer, providing rapid quenching, and reduced drag-out and fast draining, minimizing oil losses during operation.



- 12
- 24
- 64
- 45
- 65
- 20
- 27

MINERAL

ISO VG Grade
VG 46

OPTIMA THERMIC

Classification: Thermic oil

OPTIMA THERMIC Oils are mineral oil-type heat transfer oils for use in thermic systems with forced circulation, recommended for use in thermic systems where fuel oil, gas, or electricity is used to heat a fluid, which then transfers the heat to the point of application.




- 12
- 24
- 64
- 45
- 65
- 20
- 27

MINERAL

ISO VG Grade
VG 32
VG 46



PATRON[®]
POWER TO ACHIEVE



DAMAM
INTEGRATED SOLUTIONS

MENA Exclusive Partner & Distributor

DAMAM FZCO



P.O BOX 452939

**LB181402, JAFZA VIEW 18, Jebel Ali Free Zone, Dubai,
United Arab Emirates**



+971 4 321 9009



+971 4 343 0776



info@damam.ae



The Office Hours

Monday to Friday 08:00 AM to 05:00 PM

